



ASCEND ACOUSTICS, INC. www.ascendacoustics.com
 1842 W 169th St Suite B, Gardena, CA 90247 (310) 719-9786
 Email: custservice@ascendacoustics.com Fax (310) 388-1500

Sierra-1 Owner's Manual Addendum*

Specifications

Typical In-Room Frequency Response	39Hz – 22kHz +/- 3dB
In-Room Sensitivity	87dB @ 1 watt / 1 meter
Frequency Response (Anechoic)	44Hz - 22kHz +/- 3dB
Sensitivity (Anechoic)	86.5dB @ 1 watt / 1 meter
Average Impedance	8 ohms
Minimum Recommended Power	45 watts
Maximum Continuous Power*	200 watts
Maximum Short Term Peak Power*	400 watts
Cabinet	Exclusive V-LAM™ construction featuring vertically laminated bamboo. Bass Reflex via Rear Tuned Port
Dimensions H x W x D**	14.25" x 7.5" x 10.5"
Speaker Weight (each)	20 lbs each
Shipping Weight (pair)	43 lbs per pair
Tweeter	(1) 26mm high-definition soft dome tweeter w/integrated elastomer wave-guide, wide surround, low-viscosity magnetic fluid cooling, pole-piece damping chamber. Fully manufactured by SEAS of Norway
Woofers	(1) Proprietary 5.25" long throw mineral-filled polypropylene cone, non-resonant cast aluminum frame, copper shorting rings, low-inductance motor assembly, vented pole-piece and vented spider.
Connectors	(2) gold plated all metal 5 way binding posts
Inserts	(1) ¼" x 20 inserts for securing to a stand
*Unclipped peaks	**Grille Off

The Sierra-1 comes with a 7-year parts and labor warranty. Please see warranty information on the last page of the included owner's manual.

* Note: New owner's manuals for the Sierra-1 are not yet available.